



0935 253 101/... M

CAN-/DeviceNet-Thin Cable

CAN/DeviceNet Thin Cable

beidseitig umspritzt
mit 7/8"-Stecker und
M12-Kupplung, 5-polig

molded on both sides
with 7/8" male connector and
M12 female connector, 5 poles

0935 253 102/... M

CAN-/DeviceNet-Thin Cable

CAN/DeviceNet Thin Cable

beidseitig umspritzt
mit M12-Stecker und 7/8"-
Kupplung, 5-polig

molded on both sides
with M12 male connector and
7/8" female connector, 5 poles

Stecker / Kupplung, 5-polig male connector / female connector, 5 poles	Funktion Function	Farbe Color
Pin 1	Schirm / shield	
Pin 2	+ 24 V	rot / red
Pin 3	GND (0 V)	schwarz / black
Pin 4	CAN_H	weiß / white
Pin 5	CAN_L	blau / blue

Bestellbezeichnung Designation

0935 253 101/... M



0935 253 102/... M



Standardlängen: 1 M / 2 M / 3 M / 5 M
Andere Kabellängen oder Leitungsaufbauten auf Anfrage.

Standard lengths: 1 M / 2 M / 3 M / 5 M
Other cable lengths or cable specifications on request.