

## Product data sheet

Item No. R1.188.2310.0

### Device for monitoring of safety-related circuits SNV4074SL-A 3s AC 115-230V

Base unit, single-channel or two-channel control, automatic-/ manual reset with reset switch monitoring, 2 immediate switching current paths, 2 enabling current path off-delayed not retriggerable, 2 signalling contacts immediately, 2 signalling contacts off-delayed, 0 - 3s, AC 115-230 V, screw-terminals pluggable



Item No.	R1.188.2310.0
EAN	4046521300607
Order Unit	1 Piece(s)

#### Certificates / Approvals



#### Technical data

##### General

Function display	5 LED, grün/rot
Creepage distances and clearances between the circuits	EN 60664-1
Protection degree according to DIN EN 60529 (housing)	IP40
Protection degree according to DIN EN 60529 (terminals)	IP20
Ambient temperature min.	-25 °C
Ambient temperature max.	55 °C
Wire ranges screw terminals, fine-stranded / solid	1 x 0,2 mm <sup>2</sup> - 2,5 mm <sup>2</sup> / 2 x 0,2 mm <sup>2</sup> - 1,0 mm <sup>2</sup>
Wire ranges screw terminals, fine-stranded with ferrules	1 x 0,25 mm <sup>2</sup> - 2,5 mm <sup>2</sup> / 2 x 0,25 mm <sup>2</sup> - 1,0 mm <sup>2</sup>
Permissible torque min.	0.5 Nm
Permissible torque max.	0.6 Nm
Tightening moment	0.6 Nm
Weight	0.35 kg
Standards	EN ISO 13849-1EN 62061
Suited for safety functions	Yes
With muting function	No
Feedback circuit	Yes
Start contact	Yes
Stop category acc. to IEC 60204	1
Rail mounting possible	Yes

**Connection Data**

Detachable clamps	Yes
Type of electric connection	Screw connection

**Application**

Model	Basic device
Suitable for monitoring of magnetic switches	Yes
Suitable for monitoring of proximity switches	Yes
Suitable for monitoring of emergency-stop circuits	Yes
Suitable for monitoring of optoelectronic protection equipment	Yes
Suitable for monitoring of position switches	Yes

**Output circuit**

Enabling paths	Normally open contact
Enabling paths, time delayed	Normally open contact, off delay
Signaling paths	Opener
Contact material	Ag-alloy, gold-plated
Rated switching voltage, enabling paths AC	230 V
Rated switching voltage, enabling paths DC	24 V
Rated switching voltage, signaling paths AC	230 V
Rated switching voltage, signaling paths DC	24 V
Max. thermal current I	6 A
Max. thermal current I	2 A
Max. total current I <sup>2</sup> of all current path	25 A <sup>2</sup>
Application category AC-15 (NO)	Ue 230V, Ie 3A
Application category DC-13 (NO)	Ue 24V, Ie 3A
Short-circuit protection (NO), max. fuse insert	6 A class gG fuse, fuse integral < 100 A <sup>2</sup> s
Mechanical life	10 <sup>7</sup> switching cycles
Outputs, signalling function, undelayed, with contact	2
Outputs, signalling function, delayed, with contact	2
Outputs, safe, undelayed, with contact	2
Outputs, safe, delayed, with contact	2

**Control circuit**

Response time tA1	200 ms
Response time tA2	200 ms
Min. switch-on time	100 ms
Recovery time tW	> 50 ms
Release time tR	< 20 ms
Release time tR, delayed contacts (tolerance)	0,1 - 3 s (+ 0,1 %, + 15ms)
Type of switch function of the inputs	Normally open contact
Evaluation inputs	2-channel



**Supply circuit**

Nominal voltage U	AC 115-230 V
Rated consumption AC	6.3 VA
Electrical isolation supply circuit - control circuit	Yes
Min. rated control supply voltage at AC 50 Hz	98 V
Max. rated AC voltage for controls, 50 Hz	253 V
Rated control supply voltage at AC 60HZ	98 V
Rated control supply voltage at AC 50HZ	253 V

**Dimensions**

Depth	114 mm
Width	45 mm
Height	96.5 mm

**Technical drawing**

<p style="text-align: center;">⊙</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Teile-Nr. / Part-No.</th> </tr> </thead> <tbody> <tr><td>R1.188.2040.0</td></tr> <tr><td>R1.188.2070.0</td></tr> <tr><td>R1.188.2100.0</td></tr> <tr><td>R1.188.2130.0</td></tr> <tr><td>R1.188.2160.0</td></tr> <tr><td>R1.188.2190.0</td></tr> <tr><td>R1.188.2220.0</td></tr> <tr><td>R1.188.2250.0</td></tr> <tr><td>R1.188.2280.0</td></tr> <tr><td>R1.188.2310.0</td></tr> <tr><td>R1.188.2340.0</td></tr> <tr><td>R1.188.2370.0</td></tr> <tr><td>R1.188.2470.0</td></tr> <tr><td>R1.188.2500.0</td></tr> <tr><td>R1.188.2530.0</td></tr> <tr><td>R1.188.2560.0</td></tr> <tr><td>R1.188.2590.0</td></tr> <tr><td>R1.188.2620.0</td></tr> <tr><td>R1.188.2650.0</td></tr> <tr><td>R1.188.2680.0</td></tr> <tr><td>R1.188.2710.0</td></tr> <tr><td>R1.188.2740.0</td></tr> <tr><td>R1.188.2770.0</td></tr> <tr><td>R1.188.2800.0</td></tr> <tr><td>R1.188.3120.0</td></tr> <tr><td>R1.188.3510.0</td></tr> </tbody> </table>	Teile-Nr. / Part-No.	R1.188.2040.0	R1.188.2070.0	R1.188.2100.0	R1.188.2130.0	R1.188.2160.0	R1.188.2190.0	R1.188.2220.0	R1.188.2250.0	R1.188.2280.0	R1.188.2310.0	R1.188.2340.0	R1.188.2370.0	R1.188.2470.0	R1.188.2500.0	R1.188.2530.0	R1.188.2560.0	R1.188.2590.0	R1.188.2620.0	R1.188.2650.0	R1.188.2680.0	R1.188.2710.0	R1.188.2740.0	R1.188.2770.0	R1.188.2800.0	R1.188.3120.0	R1.188.3510.0	 <p style="text-align: center;">45</p>		<p style="font-size: 8px;">Werte für die Abmessungen sind in mm angegeben. Values for dimensions are in mm. Dimensions are given in mm unless otherwise stated in drawing.</p>
Teile-Nr. / Part-No.																														
R1.188.2040.0																														
R1.188.2070.0																														
R1.188.2100.0																														
R1.188.2130.0																														
R1.188.2160.0																														
R1.188.2190.0																														
R1.188.2220.0																														
R1.188.2250.0																														
R1.188.2280.0																														
R1.188.2310.0																														
R1.188.2340.0																														
R1.188.2370.0																														
R1.188.2470.0																														
R1.188.2500.0																														
R1.188.2530.0																														
R1.188.2560.0																														
R1.188.2590.0																														
R1.188.2620.0																														
R1.188.2650.0																														
R1.188.2680.0																														
R1.188.2710.0																														
R1.188.2740.0																														
R1.188.2770.0																														
R1.188.2800.0																														
R1.188.3120.0																														
R1.188.3510.0																														
<p>06 - PRE 12/92</p>		<p style="text-align: center;">Weitere Angaben siehe KATALOG oder eKatalog. Additional data see CATALOG or eCatalog.</p> <p style="text-align: right;">www.wieland-electric.com eshop.wieland-electric.com</p>																												
<p>ja/yes <input type="checkbox"/> Stoffverbots- und Deklarationsliste nach NN 5020.010 ist einzuhalten. Conformity with Wieland document NN 5020.010 e (list of prohibited / declarable hazardous substances) to be declared</p>																														
<p>Freiheiten nach General tolerance</p>		<p>CAD-Zeichnung, keine manuellen Änderungen CAD-Drawing, no manual modifications allowed</p>																												
<p>1. Verwendung: First Use:</p>		<p>Blatt: Sheet:</p>																												
<p>Werkstoff/Material</p>	<p>2014 Tag/Date</p>	<p>Name</p>	<p>Zeichnung Nr. / Drawing No.</p>																											
<p>Maßstab/Scale</p>	<p>05.06.</p>	<p>Költzner</p>	<p><b>T R1.188.3120.0 01K</b></p>																											
<p>Maße in mm/Dimensions are in mm</p>																														
<p>Detail/ File: 030021_A01K_R1.188.3120.0.DCD</p>		<p>Ersatz für/ Replacement for:</p>																												
<p>03.02.15</p>		<p>Type</p>																												
<p>03.02.15</p>		<p>Benennung/ Title</p>																												
<p>03.02.15</p>		<p>Maßbildzeichnung/dimension drawing</p>																												
<p>03.02.15</p>		<p>Standardgehäuse u. -deckel, Baubreite 45mm, Schraubklemmen steckbar</p>																												
<p>03.02.15</p>		<p>standard housing and cover, overall with 45mm plug-in pcb terminal</p>																												

R11883120001K\_1 CADW3072 Koeltzner 2015-02-04T14:01:36 1.00D